



Teknik Bilgiler / Technical Informations

DÜBEL KALINLIĞI ANCHOR THICKNESS	DÜBEL BOYU ANCHOR LENGTH	DÜBEL BORU ANCHOR HOLE	BORU KALINLIĞI PIPE THICKNESS	ANKRAJ BOYU ANCHORAGE LENGTH	BORU UZUNLUĞU PIPE LENGTH	MAX. SIKMA TORKU MAX. TIGHTENING	MAX. ÇAŞILMA YÜKÜ MAX. WORK LOAD	AĞIRLIK WEIGHT
d1	L	d	t	a	L1	Nm	kN	Gr
M 6	65,00	10,00	1,00	50,00	45,00	25,00	5,00	23,00
M 8	75,00	13,00	1,20	62,00	45,00	45,00	9,00	42,00
M 8	110,00	13,00	1,20	95,00	85,00	45,00	9,00	59,00
M 10	85,00	15,00	1,20	70,00	50,00	65,00	9,00	77,00
M 10	110,00	15,00	1,20	95,00	85,00	65,00	11,00	102,00
M 12	90,00	16,00	1,20	75,00	55,00	90,00	11,00	110,00
M 14	110,00	19,00	1,50	90,00	75,00	110,00	14,00	176,00
M 16	120,00	22,00	2,00	90,00	75,00	120,00	18,00	263,00